

BILL OF MATERIAL

| SHIP QTY. | QUAN. | PC. MARK | DESCRIPTION | LENGTH FT. IN. | REMARKS | SEQ (QTY) |
|-----------|-------|----------|-----------------------------------|-----------------------------------|---|-----------|
| | 2 | 320B1 | BEAM | | | 3A |
| 1 | 2 | 320B1 | W10x12 | 24-0 ⁹ / ₁₆ | B1E A992 | |
| | 4 | | FIELD BOLTS | | | |
| | | | $\frac{3}{4}$ Dia A325N | | 2 +2HD WASH | |
| | 2 | 320B2 | BEAM | | | 3A |
| 1 | 2 | 320B2 | W10x12 | 7-1 ¹³ / ₁₆ | A992 | |
| 1 | 2 | f41 | FL $\frac{3}{8}$ x $\frac{3}{16}$ | 6 | A36 | |
| | 4 | | FIELD BOLTS | | | |
| | 4 | | $\frac{3}{4}$ Dia A325N | | 2 +2HD WASH | |
| | 4 | | $\frac{3}{4}$ Dia A325N | | 1 ³ / ₄ +1HD WASH | |
| | 2 | 320B3 | BEAM | | | 3A |
| 1 | 2 | 320B3 | W10x39 | 19-5 | A992 | |
| 2 | 4 | f41 | FL $\frac{3}{8}$ x $\frac{3}{16}$ | 6 | A36 | |
| | 4 | | FIELD BOLTS | | | |
| | 4 | | $\frac{3}{4}$ Dia A325N | | 2 ¹ / ₄ +2HD WASH | |
| | 8 | | $\frac{3}{4}$ Dia A325N | | 1 ³ / ₄ +1HD WASH | |
| | 2 | 320B4 | BEAM | | | 3A |
| 1 | 2 | 320B4 | W10x39 | 18-7 | A992 | |

| ERECTION BOLTS | | | |
|----------------|------|--------|------|
| QUAN. | SIZE | LENGTH | TYPE |
| | | | |
| | | | |
| | | | |
| | | | |

SHOP NOTES: 1.) ALL STEEL TO BE ASTM A36 U.N.

PAINT CENTURY COATING 220-D-344 GRAY PRIMER HOLES $\frac{13}{16}$ Dia. UNL. NTD.
 SURFACE PREP SSPC SP2 & 3 UNO MIL THICKNESS $\frac{2}{16}$ TO $\frac{3}{16}$ UNO ELECTRODES E70XX/E7XT-X

SEQ.3A
 FOR APPROVAL

