



LENGTHS SHOWN ARE IN HORIZONTAL PROJECTION
DT= Danger Tag (per OSHA)

LENGTHS SHOWN ARE IN HORIZONTAL PROJECTION

FL & FR = Type S, F & R
or dimension to end of
seats from center line.

Seat Standards UNLESS NOTED ON THE LIST
BDL,BDR: H & K = 2 1/2"
LH & DLH = 5"
Slots: H & K = 5/8", 3 1/2" Gage
LH & DLH = 7/8", 4" Gage

* OSHA JOIST TO GIRDER CONNECTION
WS= Welded Seats
NS= Joist Bolted on Near Side
FS= Joist Bolted on Far Side
BS= Joist Bolted on Both Sides

Seat Standards UNLESS NOTED ON THE LIST
BDL,BDR: = 7 1/2"
SLOTS: = 7/8", 5"
THL, THR = 5/8"Holes, 4 1/2" Gage
Holes for LH Series Must be Noted



TYPE "S" EXT

TYPE "F" & "R" EXT

C/C or Clear = C/C of Grid or Inside Face of Wall
OAL Over All Length
N = Number of Joist Spacings

EXTL = **EX**ension **T**op **L**eft
CL = **C**learance **L**eft
BDL = **B**earing **D**ePTH **L**eft
SHL = **S**eat **H**oles **L**eft
BCXL = **B**ottom **C**hord **E**xension **L**eft
THL = **T**op **C**hord **H**ole **L**eft (Girder)
THL2 = **T**op **C**hord **H**ole **L**eft **2**nd (Girder)
PL = **P**anel **L**eft (Girder)

EXTR = **EX**ension **T**op **R**ight
CR = **C**learance **R**ight
BDR = **B**earing **D**ePTH **R**ight
SHR = **S**eat **H**oles **R**ight
BCXR = **B**ottom **C**hord **E**xension **R**ight
THR = **T**op **C**hord **H**ole **R**ight (Girder)
THR2 = **T**op **C**hord **H**ole **R**ight **2**nd (Girder)
PR = **P**anel **R**ight (Girder)



A Fabricator's Friend